

TECHNICAL SPECIFICATIONS

RESPONSE

Frequency response (1 W @ 1 m)	39 - 200 Hz ± 3 dB
Cut-off frequency (at -10 dB)	27 Hz
Frequency resonance of the enclosure	40 Hz
Sensibility (dB SPL 1 W @ 1 m)	94

IMPEDANCE

Impedance	8 Ohms
-----------	--------

POWER HANDLING

Power	300 W AES
Max. (dB SPL 1 W @ 1 m)	124 / 118

TRANSDUCERS

LF	1 x 12"
----	---------

ENCLOSURE

Width/Height/Depth	44 x 56 x 33
Net weight	14 kg.
Built in wood	MDF
Finish painted (water resistant treatment)	Black
Grill (perforate steel)	Open Cell Foam

ACCESSORIES

Connectors	2 x NL4 + 2 binding clip
Rigging (Industry standard stainless steel ironworks)	No
Handles	2 integrated
Rigging for floor	4 taps
Vase support for stand	1



Model **G-300** incorporates a 12" for the reproduction of low frequencies.

The unit has a low distortion level, specially design to be part of fixed installations, where a low frequencies clear response needed.

Enclosure equipped with two lateral handles and a superior vase for elevation altogether with the units that will reinforce.

The system is recommended as bass reinforcement for models **P-105** , **P-108**, **P-205**, **PE-112**

The enclosure is constructed in MDF, lateral handles; Black finish.

