

TECHNICAL SPECIFICATIONS

RESPONSE

Frequency response (1 W @ 1 m)	60 - 20.000 Hz \pm 3 dB
Frequency cut-off (at -10 dB)	48 Hz
Frequency resonance of the enclosure	65 Hz
Sensibility (dB SPL 1 W @ 1 m) Bandwidth	94 dB
Sensibility (dB SPL 1 W @ 1 m) LF	94 dB
Sensibility (dB SPL 1 W @ 1 m) M/HF	94 dB

IMPEDANCE

Impedance (Bandwidth)	8 Ohms
Impedance LF transducer	8 Ohms
Impedance M/HF transducer	8 Ohms

POWER Handling

Power (Bandwidth)	100 W AES
Max. (dB SPL 1 W @ 1 m) Bandwidth	115 / 109

COVERAGE

Horizontal (- 6 dB)	90°
Vertical (- 6 dB)	90°

TRANSDUCERS

LF	1 x 6"
M/HF	Tweeter

ENCLOSURE

Width/Height/Depth	21 x 34 x 26
Net weight	4 kg.
Built in wood	Yes
Finish painted (water resistant treatment)	Wood
Grill (perforate steel)	Open cell foam backed

ACCESSORIES

Connectors	2 binding clip
Rigging (Industry standard stainless steel ironworks)	No
Handles	No
Floor stand	4 plastic taps
Vase support for stand	No



The P-106 is a high quality system of great linearity, as required for all kinds of musical reproduction with maximum definition and accuracy.

It incorporates a 6" speaker for mid-lo frequencies and a tweeter for the hi band frequencies.

The unit has been designed with special emphasis on achieving a good tonal coherence between the two speakers.

This system is specially suitable for use as a studio monitor, in theatres, auditoriums, bars; and is specially suited for sound reproduction of any kind of instrument.

The unit is constructed in fiber, wood finish.

