

TECHNICAL SPECIFICATIONS

RESPONSE

Frequency response (1 W @ 1 m)	65 - 18.500 Hz ± 3 dB
Cut-off frequency (at -10 dB)	27 Hz
Frequency resonance of the enclosure	65 Hz
Sensibility (dB SPL 1 W @ 1 m) LF	98
Sensibility (dB SPL 1 W @ 1 m) MF	97
Sensibility (dB SPL 1 W @ 1 m) HF	102

IMPEDANCE

Impedance LF transducer	8 Ohms
Impedance MF transducer	8 Ohms
Impedance HF transducer	16 Ohms

POWER

Power (LF)	400 W AES
Power (MF)	350 W AES
Power (HF)	50 W AES
Max. (dB SPL @ 1 m) LF	127 / 121
Max. (dB SPL @ 1 m) MF	127 / 121
Max. (dB SPL @ 1 m) HF	127 / 121

COVERAGE

Horizontal (- 6 dB)	90°
Vertical (- 6 dB)	40°

TRANSDUCERS

LF Bass Reflex	1 x 12"
M Compression + horn	1" coil 55 mm

H Compression driver

ENCLOSURE

Width/Height/Depth	44 x 56 x 33
Net weight	17 kg. APROX
Built in wood	MDF
Finish painted (water resistant treatment)	Black
Grill (perforate steel)	Foam backed

ACCESSORIES

Connectors	2 x NL4 + 2 x bind.clips
Rigging (Industry standard stainless steel ironworks)	No
Handles	2 lateral
Floor stand	4 in the base
Vase for stand support	1 in the base

