

TECHNICAL SPECIFICATIONS

RESPONSE

Frequency response (1 W @ 1 m)	60 - 18.000 Hz \pm 3 dB
Cut-off frequency (at -10 dB)	53 Hz
Frequency resonance of the enclosure	55 Hz
Sensibility (dB SPL 1 W @ 1 m) LF	99
Sensibility (dB SPL 1 W @ 1 m) MF	99
Sensibility (dB SPL 1 W @ 1 m) HF	105

IMPEDANCE

Impedance LF transducer	8 Ohms
Impedance HF transducer	8 Ohms

POWER

Power (LF)	500 W AES
Power (HF)	150 W AES
Max. (dB SPL @ 1 m) LF	131 / 125
Max. (dB SPL @ 1 m) HF	134 / 128

COVERAGE

Horizontal (- 6 dB)	60°
Vertical (- 6 dB)	45°

TRANSDUCERS

LF Bass Reflex	1 x 12"
H Compression driver	2" coil 75 mm

ENCLOSURE

Width/Height/Depth	
Net weight	33 kg. APROX
Built in wood	Baltic Birch
Finish painted (water resistant treatment)	Black
Grill (perforate steel)	Foam backed

ACCESSORIES

Connectors	2 x NL4 + 2 x binding clips
Handles	2 lateral
Floor stand	8 taps

