

**TECHNICAL SPECIFICATIONS**

**RESPONSE**

Frequency response (1 W @ 1 m)	42 - 18.500 Hz $\pm$ 3 dB
Cut-off frequency (at -10 dB)	35 Hz
Recommended cut-off frequency in active	200 Hz - 24 dB
Frequency resonance of the enclosure	33 Hz
Sensibility (dB SPL 1 W @ 1 m) LF	98
Sensibility (dB SPL 1 W @ 1 m) MF	100
Sensibility (dB SPL 1 W @ 1 m) HF	106

**IMPEDANCE**

Impedance LF transducer	8 Ohms
Impedance MF transducer	8 Ohms
Impedance HF transducer	8 Ohms

**POWER**

Power (LF)	600 W AES
Power (MF)	200 W AES
Power (HF)	100 W AES
Max. (dB SPL @ 1 m) LF	125 / 131
Max. (dB SPL @ 1 m) MF	124 / 130
Max. (dB SPL @ 1 m) HF	124 / 130

**COVERAGE**

Horizontal (- 6 dB)	60°
Vertical (- 6 dB)	40°

**TRANSDUCERS**

LF Bass Reflex	1 x 18"
M Compression + horn	1 x 10"
H Compression driver	1 x 1" coil 50 mm

**ENCLOSURE**

Width/Height/Depth	54 X 104 X 54
Net weight	52 kg.
Built in wood	
Finish painted (water resistant treatment)	Black
Grill (perforate steel)	Foam backed

**ACCESSORIES**

Connectors	2 x NL4
Rigging (Industry standard stainless steel ironworks)	
Handles	
Floor stand	

